

UTILITY-SCALE ESS SOLUTION

DEYE WINTER WS SERIES



Ultimate Safety

- 3+3 Fire Protection System
- 3+3 Electrical Safety Safeguards
- AC Leakage & DC Insulation detection
- High-Voltage Interlock



Versatile Applications

- Peak Shaving & Energy Arbitrage
- Virtual Power Plant (VPP) Ready
- Off-Grid & Microgrid Capable
- PV and BESS DC Coupling
- Hybrid Solar-BESS-Diesel Systems



High Energy Density

- 4300kWh in 20' BESS container
- 2250kW PCS, 2880kW PV in 10' container



Seamless Scalability

- Modular Architecture
- Flexible 2/4/6h Energy Storage Solutions
- Compact Design, High Energy Density



Smart Cloud Management

- AI-Powered Load Optimization
- 24/7 Remote Monitoring & O&M
- Real-Time Battery Health & Safety Alerts
- Cloud-Connected Ecosystem



Cluster Management

- One cluster management, high availability, more friendly to the cell

IP55

Protection Rating

2880kW


PV DC Coupling

5 Levels


Fire Protection




Model		WS-L4300-BC-3
DC Battery		
Battery Type		LiFePO ₄
Nominal Capacity (Cell)		314Ah
Nominal Energy		4340kWh
PACK Configuration		1P48S
RACK Configuration		18 × 1P240S
Nominal DC Voltage		768Vdc
DC Voltage Range		648Vdc ~ 876Vdc
Charge and discharge rate		≤0.5P
Max. Charging / Discharging Current		3150A (18 × 175A)
No. of DC Output		18
System		
Operating Temperature		-30℃ ~ +55℃
Storage Temperature		-30℃ ~ +60℃
Humidity		0 ~ 95% (No condensation)
Type of cooling		Liquid cooling
Fire Suppression		Aerosol、Water
Ingress Protection		IP55
Anticorrosion grade		C4-M (Optional C5)
Altitude		≤2000m
Communication		CAN、RS485、TCP、DIDO
Weight		40000kg
Dimensions (W × D × H)		6058 × 2438 × 2896mm


UTILITY-SCALE ESS Solution


PV + Energy Storage + Diesel Generator Microgrid Solution




PV+ Energy Storage + Diesel Generator off-grid Solution




PV + Energy Storage Off-grid Solution




On-grid Energy Storage Solution with Backup Power




Typical Application Scenarios




6-hour Energy Storage Solution



4-hour Energy Storage Solution




2-hour Energy Storage Solution




Application Scenarios

Ideal for medium to large C&I microgrid applications


1. Applied in medium to large-scale C&I applications (Peak Shaving & Valley Filling)




2. Integrated with renewable energy storage systems to smooth power output



3. Used for Peak Shaving and Frequency Regulation on the power generation side



4. Participates in virtual power plants to provide ancillary power services (electricity trading)



www.deyeess.com / www.deyeinverter.com



Deye ESS / Deye New Energy