



Micro Hybrid Energy Storage System

# MICRO HYBRID ESS

Suitable for on-grid, off-grid, and portable use

SUN-BK80/160/200/250-2.56KWH-EU-AM4-18/32L



**Hybrid Grid-Tied Mode**  
Self-consumption



**Off-Grid Mode**  
Standalone & portable energy storage



**AC-Coupled Mode**  
Upgrade the existing PV balcony system to ESS



### Plug and Play

Installs easily with any standard socket



### Wireless Zero-Export Function

Precise control & ultra-low latency



### Time-of-Use Electricity Strategy

Sets up 6 time periods for charging/discharging



### 96.5% Conversion Efficiency

Low energy loss



### UPS-Grade Backup Power

≤4ms on-grid/off-grid switchover



### Strong Performance

Up to 2.5kW rated AC power



### Intelligent Load Control

Supports smart plug, smart switch,  
smart EV charger



### IP65 Protection Rating

10-year warranty



### 99% PV Module Compatibility

Max. 5760W PV access power



### Portable Design

Reliable power for outdoor trips



### Remote O&M

Control via Deye Cloud App



### Local Bluetooth Communication

Supports offline control

# Micro Hybrid Energy Storage System

Max. 5760W PV  
power input

2.56kWh  
LFP Battery

Max. 2500W On-grid  
& Off-grid operation



Model	SUN-BK80-2.56KWH -EU-AM4-18L	SUN-BK160-2.56KWH -EU-AM4-18L	SUN-BK200-2.56KWH -EU-AM4-18L	SUN-BK250-2.56KWH -EU-AM4-18L
-------	---------------------------------	----------------------------------	----------------------------------	----------------------------------

## Battery Input Data

Battery Type	LiFePO <sub>4</sub>			
Battery Voltage Range(V)	44.8-57.6 V			
Battery Nominal Energy (Wh)	2560Wh			
Max.Charging/Discharging Current(A)	50A			
Charging Strategy for Li-ion Battery	Self-adaption to BMS			

## PV String Input Data

Max. PV access power (W)	4400W			
Max. Operating PV Input Current (A)	18+18+18+18A			
Max. Input Short-Circuit Current (A)	32+32+32+32A			
Rated PV Input voltage (V)	42.5V			
Start-up Voltage (V)	25Vdc			
MPPT voltage range (V)	20 ~ 55V			
No. of MPP Trackers/No. of Strings MPP Tracker	4/1+1+1+1			

## AC Input/Output Data

Rated AC Input/Output Active Power (W)	800W	1600W	2000W	2500W
Max. AC Input/Output Active Power (W)	880W	1760W	2200W	2750W
Max. off grid power (W)	2500W			
Rated AC Input/Output Current (A)	3.7A / 3.5A	7.3A / 7.0A	9.1A / 8.7A	11.4A / 10.9A
Max. AC Input/Output Current (A)	4A / 3.9A	8A / 7.7A	10A / 9.6A	12.5A / 12A
Peak Power (off-grid) (W)	2 times of rated power,10s			
AC Input / Output Frequency and Voltage	50Hz ( 45Hz ~ 55Hz ) , 60Hz ( 55Hz ~ 65Hz ) , L + N + PE , 220 / 230 Vac			
Power Factor Adjustment Range	0.8 leading-0.8lagging			
Max. Continuous AC Passthrough (grid to load)(A)	30A			
DC Injection Current	<0.5%In			

## Efficiency

Max. Efficiency	96.5%			
Euro Efficiency	96.0%			
MPPT Efficiency	>99%			

## Equipment Protection

Integrated	DC reverse polarity protection, AC Output Overcurrent Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, Thermal Protection, Insulation Impedance detection, Anti-islanding protection			
Surge Protection Level	TYPE II(DC),TYPE II(AC)			

## General Data

Max. Inverter Parallel NO.	3 pcs (up to 7.5 kW rated output)			
Communication Interface	Wi-Fi, Bluetooth, LoRa			
Operating Temperature Range (°C)	-10°C ~ 55°C, >45°C Derating, (-20°C~55°C with heating, optional)			
Permissible Altitude (m)	2000m			
Ingress Protection(IP) Rating	IP 65			
Cabinet Size (W X H X D)	560 × 330 × 210mm			
Weight (kg)	30kg			
Permissible Ambient Humidity	0% ~ 95% ( No Condensing )			
Warranty	10 years			
Grid Regulation	VDE 4105, IEC 61727/62116, VDE 0126, AS 4777.2, CEI 0-21, EN 50549-1, G98, C10-11, UNE 217002			
Safety EMC/Standard	IEC 62619, UN38.3, IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1/2/3/4			

# Micro Hybrid Energy Storage System

Max. 5760W PV  
power input

2.56kWh  
LFP Battery

Max. 2500W On-grid  
& Off-grid operation



Model	SUN-BK80-2.56KWH -EU-AM4-32L	SUN-BK160-2.56KWH -EU-AM4-32L	SUN-BK200-2.56KWH -EU-AM4-32L	SUN-BK250-2.56KWH -EU-AM4-32L
<b>Battery Input Data</b>				
Battery Type	LiFePO <sub>4</sub>			
Battery Voltage Range(V)	44.8-57.6 V			
Battery Nominal Energy (Wh)	2560Wh			
Max.Charging/Discharging Current(A)	50A			
Charging Strategy for Li-ion Battery	Self-adaption to BMS			
<b>PV String Input Data</b>				
Max. PV access power (W)	5760W			
Max. Operating PV Input Current (A)	32+32+32+32A			
Max. Input Short-Circuit Current (A)	48+48+48+48A			
Rated PV Input voltage (V)	42.5V			
Start-up Voltage (V)	25Vdc			
MPPT voltage range (V)	20 ~ 55V			
No. of MPP Trackers/No. of Strings MPP Tracker	4/1+1+1+1			
<b>AC Input/Output Data</b>				
Rated AC Input/Output Active Power (W)	800W	1600W	2000W	2500W
Max. AC Input/Output Active Power (W)	880W	1760W	2200W	2750W
Max. off grid power (W)	2500W			
Rated AC Input/Output Current (A)	3.7A / 3.5A	7.3A / 7.0A	9.1A / 8.7A	11.4A / 10.9A
Max. AC Input/Output Current (A)	4A / 3.9A	8A / 7.7A	10A / 9.6A	12.5A / 12A
Peak Power (off-grid) (W)	2 times of rated power,10s			
AC Input / Output Frequency and Voltage	50Hz ( 45Hz ~ 55Hz ) , 60Hz ( 55Hz ~ 65Hz ) , L + N + PE , 220 / 230 Vac			
Power Factor Adjustment Range	0.8 leading-0.8lagging			
Max. Continuous AC Passthrough (grid to load)(A)	30A			
DC Injection Current	<0.5%In			
<b>Efficiency</b>				
Max. Efficiency	96.5%			
Euro Efficiency	96.0%			
MPPT Efficiency	>99%			
<b>Equipment Protection</b>				
Integrated	DC reverse polarity protection, AC Output Overcurrent Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, Thermal Protection, Insulation Impedance detection, Anti-islanding protection			
Surge Protection Level	TYPE II(DC),TYPE II(AC)			
<b>General Data</b>				
Max. Inverter Parallel NO.	3 pcs (up to 7.5 kW rated output)			
Communication Interface	Wi-Fi, Bluetooth, LoRa			
Operating Temperature Range (°C)	-10°C ~ 55°C, >45°C Derating, (-20°C~55°C with heating, optional)			
Permissible Altitude (m)	2000m			
Ingress Protection(IP) Rating	IP 65			
Cabinet Size (W X H X D)	560 × 330 × 210mm			
Weight (kg)	30kg			
Permissible Ambient Humidity	0% ~ 95% ( No Condensing )			
Warranty	10 years			
Grid Regulation	VDE 4105, IEC 61727/62116, VDE 0126, AS 4777.2, CEI 0-21, EN 50549-1, G98, C10-11, UNE 217002			
Safety EMC/Standard	IEC 62619, UN38.3, IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1/2/3/4			

Supports up to 5 batteries for vertical stacking expansion and up to 8 clusters (40 batteries) via cable connection



Model	AE-F2.56
<b>Battery Technical Specification</b>	
Battery Chemistry	LiFePO <sub>4</sub>
Battery Nominal Voltage	51.2V
Battery Nominal Energy	2560Wh
Max. Charging / Discharging Current	50A
Battery Operating Voltage	44.8V ~ 57.6V
Battery Cycle Life	≥6,000 (@25°C±2°C, 70%EOL)
Max. Stack NO.	5 pcs (up to 12.8kWh)
Parallel Capability	40 pcs*
<b>Other Technical Specification</b>	
Display	LED ( SOC, Alarm )
Communication Interfaces	LoRa
Dimension ( W × D × H ) (mm)	450 × 210 × 244 (without terminal)
Ingress Protection(IP) Rating	IP 65
Weight Approximate	22±3 kg
Operating Temperature Range	-10°C~55°C ( -20°C~55°C with heating, optional)
Max. Operating Altitude	2,000m
Relative Humidity	0% ~ 95% ( No Condensing )
Certification	UN38.3, IEC 62619, CE
Installation Style	Floor-Mounted, Stacked-Mounted
Warranty	10 years

\*Maximum 40 Pieces AE-F2.56 Packs in Parallel, Up to 102.4kWh.



App Interface Subject to Change

## SCENARIO-BASED ENERGY MANAGEMENT SOLUTIONS

Utilize energy in every outdoor adventure or household needs. Embrace effortless energy experience that's both eco-friendly and budget-friendly with our intelligent assistant.

**Scenario 1 :**



**Compact Balcony Solar Plant**  
**Automated Energy-Saving Strategies**

**Scenario 2 :**



**Camping Power Solution**  
**Empower Your Outdoor Adventure**

**Scenario 3 :**



**Reliable Home Emergency Power Source**  
**Ensure You Stay Powered Up When You Need It Most**



\* Selling electricity back to grid is available where local regulations permit.

### One-Tap Setup, Real-Time Optimization

#### Flexible Scheduling

Sets up 6 customizable charging/discharging time slots to utilize time-of-use electricity pricing and reduce costs.

#### Deye Copilot Function

Enables Deye Cloud to access local dynamic electricity prices and intelligently decide the optimal time for electricity trading.



Join Deye's Intelligent Energy Revolution and Start Saving Today!





# What Can It Power

Max. 2.5 kW/ 2.56 kWh

1 Inverter + 1 Battery Design



## Typical Device Runtime

No Electricity Anxiety for Emergency Power Backup



Phone

135 Times



Laptop

23 Times



Light

3 Days



TV

7.5 Hours



Camera

133 Times



UAV

20 Times



Microwave

1.8 Hours



Mini Refrigerator

1-2 Days



Wi-Fi Router

3 Days



Space Heater

25 Hours

\* The data above is for reference only. Actual runtime may vary with use.

## Compatible Appliances



Kitchen Appliances



Household Appliances



Office & Entertainment



Lighting & Small Electronics

Electric kettle  
1800W

Hair dryer  
1800W

Wi-Fi router  
10W

Light  
10W DC

Microwave oven  
1000W

Vacuum cleaner  
1000W

Laptop  
60W

Phone charger  
25W

Blender  
500W

Air purifier  
100W

Printer  
50W

Fan  
40W

Rice cooker  
800W

Space heater  
1500W

Projector  
300W

Loudspeaker  
60W

Air fryer  
1500W

Washing machine  
500W

Television  
120W

Tablet  
45W

### Key Power Note:

The rated powers above are for reference only. All devices with a rated power of  $\leq 2500W$  are compatible. Operational Safety: Ensure the total power of all devices running simultaneously stays under 2500W.