

SMALL-SCALE C&I ESS SOLUTION

DEYE SUMMER BOS SERIES



Convenient

- Quick installation standard of 19-inch embedded designed module is comfortable for installation and maintenance.



Intelligent BMS

- It has protection functions including over-discharge, over-charge, over-current and over-high or low temperature. The system can automatically manage charge and discharge state and balance current and voltage of each cell.



Eco-friendly

- The whole module is non-toxic, non-polluting and environmentally friendly.



Safe and reliable

- Cathode material is made from LiFePO4 with safety performance and long cycle life. The module has less self-discharge, up to 6 months without charging it on shelf, no memory effect, excellent performance of shallow charge and discharge.



Flexible configuration

- Multiple battery modules can be in parallel for expanding capacity and power. Support USB upgrade, remote up grade (Compatible with Deye inverter).



Wide temperature

- Working temperature range is from -20°C to 55°C, with excellent discharge performance and cycle life.

≥6000

Cycles

Flexible
Expansion

35kWh ~ 87kWh

70%

EOL

10 years

Warranty for long-term
peace of mind




Rack-Mounted Battery (HV)

Model		BOS-G-Pro											
Main Parameter													
Cell Chemistry	LiFePO ₄												
Module Energy (kWh)	5.12												
Module Nominal Voltage (V)	51.2												
Module Capacity (Ah)	100												
Battery Module Number	BOS-G25-Pro	BOS-G30-Pro	BOS-G35-Pro	BOS-G40-Pro	BOS-G45-Pro	BOS-G50-Pro	BOS-G55-Pro	BOS-G60-Pro	BOS-G65-Pro	BOS-G70-Pro	BOS-G75-Pro	BOS-G80-Pro	
Battery Module Qty In Series (Optional)	5 (Min)	6	7	8	9	10	11	12	13	14	15	16 (Max)	
System Nominal Voltage (V)	256	307.2	358.4	409.6	460.8	512	563.2	614.4	665.6	716.8	768	819.2	
System Operating Voltage (V)	220-292	264-350.4	308-408.8	352-467.2	396-525.6	440-584	484-642.4	528-700.8	572-759.2	616-817.6	660-876	704-934.4	
System Energy (kWh)	25.6	30.72	35.84	40.96	46.08	51.2	56.32	61.44	66.56	71.68	76.8	81.92	
System Usable Energy (kWh)	25.6	30.72	35.84	40.96	46.08	51.2	56.32	61.44	66.56	71.68	76.8	81.92	
Rated DC Power (kW)	25.6	30.72	35.84	40.96	46.08	51.2	56.32	61.44	66.56	71.68	76.8	81.92	
Charge / Discharge ²	Recommend	50											
	Nominal	100											
Current (A)	Peak Discharge (2 mins, 25°C)	125											
Working Temperature (°C)	Charge : 0 ~ 55 / Discharge : -20 ~ 55												
Status Indicator	Yellow : Battery High Voltage Power On Red : Battery System Alarm												
Communication Port	CAN2.0 / RS485												
Humidity	5% ~ 85%RH												
Altitude	≤3000m												
IP Rating of Enclosure	IP20												
Dimension (W×D×H,mm)	530 × 602 × 1629				530 × 602 × 2219				1060 × 602 × 1629				
Weight Approximate (kg)	290	336	382	428	484	530	576	622	699	745	791	837	883
Installation Location	Rack Mounting												
Storage Temperature (°C)	0 ~ 35												
Recommend Depth of Discharge	100%												
Cycle Life	25±2°C, 0.5C / 0.5C, EOL70%≥6000												
Warranty	10 years												
Certification	UN38.3 / CE / CE-EMC / IEC62040 / CEC / VDE												

1. DC Usable Energy, test conditions : 100% DOD, 0.3C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.
2. The current is affected by temperature and SOC.
3. The warranty is due whichever reached first of warranty period or life cycle power.
4. Made in China.


Model	Description
-------	-------------

BOS-G-PDU-2	High Voltage Battery cluster control box conforming to European or British Standards
Operating Voltage	200 ~ 1000Vdc
Nominal Charge/Discharge Current	100A
Max.Charge/Discharge Current	120A
DC Input Rating	12±2%V / 4.15A
Operating Temperature Range	-20 ~ 65°C
Ingress Protection	IP20
Dimension (W×D×H)	440×570×150mm
Weight Approximate	19kg




High voltage box Standard configuration:

- ① 120 ohm terminal resistance
- ② 250mm communication cable
- ③ 140mm power cable
- ④ 2.1m power cable
- ⑤ EPCable2.0
(Standard 2-meter power cable connected to the positive pole of the external PCS)
- ⑥ ENCable2.0
(Standard 2-meter power cable connected to the negative pole of the external PCS)
- ⑦ 1000mm communication cable between two battery racks
- ⑧ 1000mm power cable between the two battery racks
- ⑨ 140 mm ground wire



BOS-G-Pack5.1	5.12 kwh battery module
----------------------	-------------------------

Battery Type	LiFePO ₄ (LFP)
Nominal Voltage	51.2Vdc
Rated Capacity	100Ah
Rated Energy	5.12kWh
Nominal Charge/Discharge Current	100A
Peak.Discharge Current	120A
Charge Temperature	0 ~ 55°C
Discharge Temperature	-20°C ~ 55°C
Storage Temperature	0°C ~ 35°C
Ingress Protection	IP20
Dimension (W×D×H)	440×585×133mm
Weight Approximate	46kg




Battery module Standard configuration:

- ① 160mm communication cable
- ② 200mm power cable

Model	Description
-------	-------------


3U-HRACK(Optional)	Standard 19inch rack, caninstall 12 pcs batteries and 1 pcs High Voltage Battery cluster control box
---------------------------	--

Dimension (W×D×H) Weight Approximate	530×602×2219mm 51kg
---	------------------------



3U-LRACK(Optional)	Standard 19inch rack, caninstall 8 pcs batteries and 1 pcs High Voltage Battery cluster control box
---------------------------	---

Dimension (W×D×H) Weight Approximate	530×602×1629mm 41kg
---	------------------------





To Make ESS Better



Deye ESS Facebook



Deye ESS



www.deyeess.com