GB-L





- **Safety**

Built in explosion relief device to dredge gas, and built in fire protection device to cut off the fire source for 3 seconds

- **High-voltage stack**

Modules are connected in series without cable connection, and high -voltage platform improves system efficiency.

- **Thermal management**

Temperature detection of key parts, cell, power plug-in, etc.

- **Wide temperature operation**

The heating function is optional to meet the application scenarios with low temperature and no sense.

- **Environmental friendliness**

IP protection grade 65, anti-corrosion grade ≥C2, environmental protection battery.

- **Intelligent and visual**

Support remote upgrade, real-time battery warning information push, LCD data display.

Deye

Technical Data

Model		GB-L				
Main Parameter						
Cell Chemistry		LiFePO4				
Module Energy(kWh)		4.09				
Module Nominal Voltage (V)		102.4				
Module Capacity(Ah)		40				
Battery Module Qty In Series (Optional)		2	3	4	5	6
System Nominal Voltage (V)		204.8	307.2	409.6	512	614.4
System Operating Voltage (V)		166.4~700				
System Energy (kWh)		8.18	12.27	16.36	20.45	24.56
System Usable Energy (kWh)[1]		7.36	11.04	14.72	18.40	22.10
Charge/Discharge Current (A)[2]	Recommend	20				
	Nominal	40				
	Peak Discharge (2 mins,25°C)	50				
Working Temperature(°C)		Charge: 0~55/Discharge: -20~60				
LCD Display		SOC%,Power,Total Voltage				
Communication Port		CAN2.0, RS485				
Humidity		5%~90%				
Altitude		≤2000m				
IP Rating of Enclosure		IP65				
Storage Temperature(°C)		0~35				
Dimension (W/D/H,mm)		540*385*650	540*385*870	540*385*1090	540*385*1310	540*385*1530
Weight(kg)		97	136	175	214	253
Installation Location		Floor Mount				
Recommend Depth of Discharge		90%				
Cycle Life		25±2°C,0.5C/0.5C, EOL70%≥6000				
Warranty[3]		10years				
Certification		CE/IEC62619 /VDE2510-50/ UL1973/UL9540A/UN38.3				

1 DC Usable Energy, test conditions: 90% DOD, 0.2C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

2 The current is affected by temperature and SOC.

3 The warranty is due whichever reached first of warranty period or life cycle power.

Deye
NINGBO DEYE ESS TECHNOLOGY CO., LTD
NO. 18TH ZHENGLONG ROAD LONGHSAN CIXI NINGBO ZHEJAING 315311 P.R.CHINA
Tel: +86-0574-8622 9263 | E-mail: sales@deye.com.cn

System Components

Model	Description
GB-LBS	High voltage battery cluster control box

Operating Voltage	120 ~ 750Vdc
Nominal Charge/Discharge Current	40A
Max Charge/Discharge Current	50A
Operating Temperature Range	-20~65°C
Ingress Protection	IP65
Dimension (W/D/H)	540*385*110mm
Weight Approximate	12kg



GB-LM4.0	4.09 kWh battery module

Battery Type	LiFePO4(LFP)
Nominal Voltage	102.4Vdc
Rated Capacity	40Ah
Rated Energy	4.09kWh
Nominal Charge/Discharge Current	40A
Peak Discharge Current	50A
Charge Temperature	0~55°C
Discharge Temperature	-20℃ ~ 60°C
Storage Temperature	0℃ ~ 35°C
Ingress Protection	IP65
Dimension (W/D/H)	540*385*220mm
Weight Approximate	39kg



GB-LBase	Battery module base

Dimension (W/D/H)	540*385*100mm
Weight Approximate	7kg

ECOM Cable2.0	Standard 2-meter commumication cable connected to the external device

EPCable2.0	Standard 2-meter power cable connected to the positive pole of the external PCS

1000V/6AWG Cable

ENCable2.0	Standard 2-meter power cable connected to the negative pole of the external PCS

1000V/6AWG Cable